XSLT

Web Data Management and Distribution

Serge Abiteboul Ioana Manolescu Philippe Rigaux
Marie-Christine Rousset Pierre Senellart

Web Data Management and Distribution
http://webdam.inria.fr/textbook

June 23, 2010

What is XSLT?

XSLT = a specialized language for transforming an XML document into another XML document.

Main principles:

- An XSLT program, or stylesheet, consists of rules, or templates.
- A template applies to a specific kind of node of the input document, and produces a fragment of the output document.
  - by creating literal nodes,
  - by copying values and fragments from the input document,
  - by instantiating (= calling) other templates.
- Execution model: initially, a template is applied to the root node of the input document
  $\Rightarrow$ this first template may initiate a traversal of the input document.

Remark

An XSLT stylesheet is an XML document! XSLT element names are prefixed by `xsl:`, the XSLT namespace.

A Hello World! Stylesheet

```
<?xml version="1.0" encoding="utf-8"?>

<xsl:stylesheet
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  version="1.0">

  <xsl:output method="xml" encoding="utf-8" />

  <xsl:template match="/">
    <hello>world</hello>
  </xsl:template>

</xsl:stylesheet>
```

General structure of a stylesheet:

- A top-level `<xsl:stylesheet>` element, with a `version="1.0"` attribute.
- Some declarations (all elements except `<xsl:template>` ones),

Invocation of an XSLT Stylesheet

An XSLT stylesheet may be invoked:

- Programmatically, through one of the various XSLT libraries.
- Through a command line interface.
- In a Web Publishing context, by including a styling processing instruction in the XML document

```
<?xml-stylesheet
  href="toto.xsl" type="text/xsl" ?>

<doc>
  <titi />
</doc>
```

  - the transformation can be processed on the server side by a CGI, PHP, ASP, JSP... script
  - or on the client side through the XSLT engines integrated to most browsers.

Web Publishing with XSLT





The `<xsl:template>` Element

```
<xsl:template  match="book">
  The book title is:
     <xsl:value-of select="title" />

   <h2>Authors list</h2>
    <ul>
      <xsl:apply-templates select="authors/name" />
    </ul>
</xsl:template>
```

A template consists of

A pattern an XPath expression (restricted) which determines the node to which the template applies.
The pattern is the value of the `match` attribute.

A body an XML fragment (well-formed!) which is inserted in the output document when the template is instantiated.

XPath patterns in XSLT

The role of the XPath expression of the `match` attribute is quite specific: it describes the nodes which can be the target of a template instantiation.
Those expressions are called patterns. They must comply to the following requirements

- A pattern always denotes a node set.
  Example: `<xsl:template match='1'>` is incorrect.
- It must be easy to decide whether a node is denoted or not by a pattern.
  Example: `<xsl:template match='preceding::*[12]'>` is meaningful, but quite difficult to evaluate.

Patterns syntax

A pattern is a valid XPath expression which uses only the `child` and `@` axes, and the abbreviation `//`. Predicates are allowed.

Pattern examples

Recall: a pattern is interpreted as the nodes to which a template applies.

- `<xsl:template match='B'>`
  applies to any B element.
- `<xsl:template match='A/B'>`
  applies to any B element, child of an A element.
- `<xsl:template match='@att1'>`
  applies to any att1 attribute, whatever its parent element.
- `<xsl:template match='A//@att1'>`
  applies to any att1 attribute, if its parent element is a descendant of an A element.

General rule

Given an XML tree T, a pattern P matches a node N if there exists a node C (the context node) in T such that $N \in P(T, C)$.

Content of a template body

Basically, the content of `<xsl:template>` may consist of:

- Literal elements and text.
  Example: `<h2>Authors</h2>`. This creates in the output document an element h2, with a **Text** child node 'Authors'.
- Values and elements from the input document.
  Example: `<xsl:value-of select='title'/>`. This inserts in the output document a node set, result of the XPath expression `title`.
- Call to other templates.
  Example: `<xsl:apply-templates select='authors'/>`. Applies a template to each node in the node set result of the XPath expression `authors`.

Remark

Only the basic of XSLT programming! Many advanced features (modes, priorities, loops and tests) beyond this core description.

Instantiation of a `<xsl:template>`

Main principles:

- Literal elements (those that don't belong to the XSLT namespace) and text are simply copied to the output document.
- Context node: A template is always instantiated in the context of a node from the input document.
- XPath expressions: all the (relative) XPath expression found in the template are evaluated with respect to the context node (an exception: `<xsl:for-each>`).
- Calls with `xsl:apply-templates`: find and instantiate a template for each node selected by the XPath expression `select`.
- Template call substitution: any call to other templates is eventually replaced by the instantiation of these templates.

The `xsl:apply-templates` element

```
<xsl:apply-templates select="authors/name" />
```

select an XPath expression which, if relative, is interpreted with respect to the context node,
Note: the default value is `child::node()`, i.e., select all the children of the context node

mode a label which can be used to specify which kind of template is required.

The `xsl:apply-templates` mechanism

```
<xsl:template match="book">
  <ul><xsl:apply-templates
            select="authors/name" /></ul>
</xsl:template>

<xsl:template match="name">
  <li><xsl:value-of select="." /></li>
</xsl:template>
```

```
<book>
...
 <authors>
  <name>Serge</name>
  <name>Ioana</name>
 </authors>
</book>
```



```
<ul>
  <li>Serge</li>
  <li>Ioana</li>
</ul>
```

Combined templates instantiation




```
<xsl:template match="book">
Title: <xsl:value-of
          select="title" />

<h2>Authors</h2>
 <ul><xsl:apply-templates
   select="authors/name" />
 </ul>
</xsl:template>
```

→

```
Title:  Web[...]

<h2>Authors</h2>
 <ul>
   <li>Serge</li>
   <li>Ioanna</li>
 </ul>
```

The execution model of XSLT

An XSLT stylesheet consists of a set of templates. The transformation of an input document *I* proceeds as follows:

1. The engine considers the root node *R* of *I*, and selects the template that applies to *R*.
2. The template body is copied in the output document *O*.
3. Next, the engine considers all the `<xsl:apply-templates>` that have been copied in *O*, and evaluate the `select` XPath expression, taking *R* as context node.
4. For each node result of the XPath evaluation, a template is selected, and its body replaces the `<xsl:apply-templates>` call.
5. The process iterates, as new `<xsl:apply-templates>` may have been inserted in *O*.
6. The transform terminates when *O* is free of `xsl:` instructions.

The execution model: illustration



The execution model: illustration



The execution model: illustration



The execution model: illustration



The execution model: illustration



The execution model: illustration



The input document in serialized and tree forms

```
<?xml version="1.0"
    encoding="utf-8"?>
<book>
  <title>Web [...]</title>
  <authors>
    <name>Serge</name>
    <name>Ioana</name>
  </authors>
  <content>
    <chapter id="1">
      XML data model
    </chapter>
    <chapter id="2">
     XPath
    </chapter>
  </content>
</book>
```



The XSLT template that matches the root node

```
<xsl:template match="/">
 <html>
   <head>
     <title>
      <xsl:value-of select="/book/title"/>
     </title>
    </head>
    <body bgcolor="white">

     <xsl:apply-templates select="book"/>

    </body>
  </html>
</xsl:template>
```

Remark

Typical of Web publishing templates.

The output document after instantiating the template



The output document after evaluation of `<xsl:value-of>`



The remaining templates

```
<xsl:template  match="book">
  Title:
     <xsl:value-of select="title" />

   <h2>Authors list</h2>
    <ul>
      <xsl:apply-templates select="authors/name" />
    </ul>
</xsl:template>

<xsl:template match="authors/name">
 <li><xsl:value-of select="."/></li>
</xsl:template>
```

The `<book>` element is selected ⇒ the book template is instantiated



The `authors/name` template is instantiated twice, one for each author



The final output document